

What we claim is:

1. A feeding amount controlling apparatus comprising:

feeding means for feeding a material;

5 detecting means for detecting feeding rate of the material ;

first calculating means for calculating a total fed amount
based on the feeding rate detected by the detecting means;

stopping means for stopping feeding the material;

second calculating means for calculating a preset amount by
10 multiplying the feeding rate detected by the detecting means
and delay time of the stopping means together; and

controlling means for generating the signal for working the
stopping means when the total fed amount calculated by the first
calculating means reaches a value defined as the difference
15 between an intended amount and the preset amount calculated by
the second calculating means.

2. A feeding amount controlling apparatus as defined in claim
1, wherein the feeding means comprises feeding rate shifting
20 mechanism for shifting the feeding rate and the controlling means
is capable of operating the feeding rate shifting mechanism in
order to shift the rate from high rate to low one when the total
fed amount reaches a value defined as the difference between
the intended amount and an alerting amount.

25

3. A feeding amount controlling apparatus as defined in claim
2, wherein the controlling means is also capable of comparing
the intended amount to the alerting amount at the start to measure

the feeding amount and of operating the feeding rate shifting mechanism in order to shift the rate from high rate to low one when the intended amount is less than or equal to the alerting amount.

5

Sub
a1

4. A feeding amount controlling apparatus as defined in claim 2 or 3, wherein the feeding rate shifting mechanism comprises larger diameter valve and smaller diameter valve which are respectively installed in main feeding line and by-pass feeding line thereof and can shift the feeding rate from high rate to low one by closing the large diameter valve.

5. Method for controlling a feeding amount of material comprising steps of :

15 detecting a feeding rate;

calculating a total fed amount based on the detected feeding rate;

shifting the feeding rate from high to low when the total fed amount reaches a value of difference between the intended amount and the alerting amount;

calculating a preset amount based on the detected feeding rate and delay time of stopping means to stop feeding the material; and

generating a signal to work the stopping means when the calculated total fed amount reaches a value of difference between the intended amount and the preset amount.

6. Method for controlling a feeding amount of material

comprising steps of :

determining whether an intended amount is larger than an alerting amount;

opening stopping means to allow the material to be fed at
5 high feeding rate if the intended amount is larger than the alerting amount ;

detecting a feeding rate;

calculating a total fed amount based on the detected feeding rate;

10 shifting the feeding rate from high to low when the total fed amount reaches a value of difference between the intended amount and the alerting amount;

calculating a preset amount based on the detected feeding rate and delay time of stopping means to stop feeding the material;

15 and

generating a signal to work the stopping means when the calculated total fed amount reaches a value of difference between the intended amount and the preset amount.

20 7. Method for controlling a feeding amount of material comprising steps of :

Determining whether an intended amount is larger than an alerting amount;

opening feeding means to allow the material to be fed at low
25 feeding rate if the intended amount is less than or equal to the alerting amount ;

detecting a feeding rate;

calculating a total fed amount based on the detected feeding

rate;

calculating a preset amount based on the detected feeding rate and delay time of stopping means to stop feeding the material; and

5 generating a signal to work the stopping means when the calculated total fed amount reaches a value of difference between the intended amount and the preset amount.

8. Method for controlling a feeding amount of material
10 comprising steps of :

Determining whether an intended amount is larger than an alerting amount;

opening feeding means to allow the material to be fed at high feeding rate if the intended amount is larger than the alerting
15 amount ;

detecting a feeding rate;

calculating a total fed amount based on the detected feeding rate;

shifting the feeding rate from high to low when the total
20 fed amount reaches a value of difference between the intended amount and the alerting amount;

calculating a preset amount based on the detected feeding rate and delay time of a stopping means to stop feeding the material, and a predicted feeding amount based on the detected feeding
25 rate;

determining whether the intended amount is larger than a summation of calculated total fed amount, the preset amount and the predicted amount;

determining timing that when a signal for working the
stopping means should be generated based on a remaining amount
to be fed before generating the signal and the predicted feeding
amount if the intended amount is less than or equal to the summation
5 in the previous step.

9. Method for controlling a feeding amount of material
comprising steps of :

determining whether an intended amount is larger than an
10 alerting amount;

opening feeding means to allow the material to be fed at low
feeding rate if the intended amount is less than or equal to
the alerting amount ;

detecting a feeding rate;
15 calculating a total fed amount based on the detected feeding
rate;

calculating a preset amount based on the detected feeding
rate and delay time of a stopping means to stop feeding the material,
and a predicted feeding amount based on the detected feeding
20 rate;

determining whether the intended amount is larger than a
summation of calculated total fed amount, the preset amount and
the predicted amount;

determining timing that when a signal for working the
25 stopping means should be generated based on a remaining amount
to be fed before generating the signal and the predicted feeding
amount if the intended amount is less than or equal to the summation
in the previous step.

Sub
a2

10. Method as defined in claims 8 or 9, wherein the step of determining timing is made by calculating Δt according to the following equation: $\Delta t = (A - PV - V_{pr}) / V_r$, wherein A is the intended amount, PV is the total fed amount, V_{pr} is the preset amount and V_r is the predicted feeding amount.

11. Method as defined in claims 10, wherein the steps until the step of determining whether the intended amount is larger than a summation of calculated total fed amount, the preset amount and the predicted amount are performed at slow scanning rate and the rest of the steps are performed at fast scanning rate.

15

09035641.082801